

Innovating
the Residential Automation
Market for Automated Doors,
Windows and Screens

Simple and affordable systems while
maintaining quality and reliability.



ABOUT AUTOHOMATION

AutoHOMATION is headquartered in Silicon Valley with offices in Santa Clara, CA and Chennai, Tamil nadu, India. AutoHOMATION provides the market with Smart Automation Technology for Residential Patio Doors, Windows, & Screens.

AutoHOMATION has currently introduced two automatic sliding door openers: Prime Lock and Multi-Controller, which enables automated open/close of siding doors with easy do-it-yourself installation.

AutoHOMATION
2227 Bellington ct San Jose
CA 95138,
(+1) 408.386.3278

AutoHOMATION Products Pvt Ltd.
3B Mahaveer Garden,
Ambattur, Chennai,
Tamil Nadu 600 058, India
(+91) 44 4863 8822

AH PRIME LOCK

Rack & pinion system designed to automate a single-panel door up to 96 inches in width.



ONE YEAR
WARRANTY



20 lbs. MAX
PULL FORCE



PET MODE



BENEFITS

- Easy to install, without changing the existing door structure.
- Compact size, aesthetic appearance and modern design.
- Remote control Operation.
- The system can be applied with sensor, remote control, push button, pet sensor, photocell, lock.

TECHNICAL FEATURES

OPERATING MODES



AUTOMATIC
MODE



MANUAL
MODE



LOCKED



PET
MODE



HOLD
OPEN

TECHNICAL SPECIFICATIONS

Power Supply	Input: 100-240 V AC; Output: 24 V DC
Max. Door Drag	20 lbs. / 9 kg
Max. Door Weight	176 lbs. / 80 kg
Max. Door Width	16.40 ft / 5 m
Standard Track	3.2 ft/ 1 m. length can be customized
Length of the track	1.6 ft/ 0.5 m per piece
Color Options	Full Black / Full White
Opening Speed	3.93 - 16.14 in/s 10 - 41 cm/s, adjustable
Closing Speed	4.72 - 8.66 in/s 12 - 22 cm/s, adjustable
Product Weight	6.614 lbs. / 3 kg
Product measurement	27.8 in/s/ 707mm

Functional Details

Automatic	●	LED Display	—
Always Open	●	Photo Cell	●
Pet	●	UPS	●
Full Lock	●	Electronic lock	●
Manual	●	OEM Service	●
Self - Learning	●	CE Certification	●
Self lock	—	Toggle Mode	●
Error message	●	Beep	●
Fire Alarm Terminal	—		
Access keypad Terminal	—		
Inter lock function	—		

●: standard function ○: optional function —: no function

AH MULTI-CONTROLLER

Belt drive controller to open single-panel and bi-parting doors.




ONE YEAR
WARRANTY



45 lbs. MAX
PULL FORCE



PET MODE



BENEFITS

- Innovative & Modern Design for Door Automation
- Globally trusted high-power Brushless DC Motors.
- Easy for installation, without change existing door structure
- Can be applied for multi-panel doors and windows
- System can apply with sensor, remote control, push button, pet sensor, photocell, lock.

AH MULTI-CONTROLLER



TECHNICAL FEATURES

OPERATING MODES



AUTOMATIC
MODE



MANUAL
MODE



LOCKED



PET
MODE



HOLD
OPEN

TECHNICAL SPECIFICATIONS

Power Supply	Input: 100-240 V AC; Output: 24 V DC
Max. Door Drag	45 lbs. / 20.4 kg
Max. Door Weight	176 lbs. / 80 kg (single)
Max. Door Width	16.40 ft / 5 m
Standard Track	7.2 ft / 2.2 m. length can be customized
Length of the track	7.2 ft / 2.2 m per piece
Color Options	Full Black / Full White
Opening Speed	3.93 - 16.14 in/s 10 - 41 cm/s, adjustable
Closing Speed	4.72 - 8.66 in/s 12 - 22 cm/s, adjustable
Product Weight	6.614 lbs. / 3 kg
Product Measurement	52.2 in/s/ 1327mm

Functional Details

Automatic	●	LED Display	—
Always Open	●	Photo Cell	●
Pet	●	UPS	●
Full Lock	●	Electronic lock	●
Manual	●	OEM Service	●
Self - Learning	●	CE Certification	●
Self lock	—	Toggle Mode	●
Error message	●	Beep	●
Fire Alarm Terminal	—		
Access keypad Terminal	—		
Inter lock function	—		

●: standard function ○: optional function —: no function